

# MICHELIN INFLATION CHARTS FOR RV USAGE ONLY

For RV use only, Michelin displays tire loads per axle end in the load and inflation tables, as we recommend weighing each axle end separately and using the heaviest end weight to determine the axle's cold inflation tire pressure. For control of your RV, it is critical the tire pressures be the same across an axle, while NEVER exceeding the maximum air pressure limit stamped on the wheels.

To select the proper load and inflation table, locate your tire size in the following pages, then match your

tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation

In the load and inflation tables, **SINGLE** means an axle with one tire mounted on each end, while **DUAL** means an axle with two tires mounted on each end. The loads indicated represent the total weight of an axle end, in an RV application. When one axle end weighs more than the other, use the heaviest of the two end weights to determine the unique tire pressure for all tires on the axle. The maximum cold air pressure for each axle may vary, depending on their weights. These tables are applicable for all RV axles, whether or not they are power-driven.

## WHEEL DIAMETER - 16"

### LT215/85R16 LRE XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		240	280	310	340	380	410	450	480	520	550	S	2680	LBS at	80	PSI
LBS	SINGLE	1495	1640	1785	1940	2055	2180	2335	2430	2550	2680	D	2470	LBS at	80	PSI
	DUAL	2720	2980	3250	3530	3723	3970	4300	4420	4640	4940	S	1215	KG at	550	kPa
kPa	SINGLE	678	744	809	880	932	989	1059	1102	1156	1215	D	1120	KG at	550	kPa
	DUAL	1234	1351	1474	1601	1689	1801	1950	2005	2104	2240					

### LT225/75R16 LRE XPS RIB®

PSI		40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		280	310	350	380	410	450	480	520	550	S	2680	LBS at	80	PSI
LBS	SINGLE	1650	1790	1940	2060	2190	2335	2440	2560	2680	D	2470	LBS at	80	PSI
	DUAL	3000	3260	3530	3750	3990	4300	4440	4660	4940	S	1215	KG at	550	kPa
kPa	SINGLE	748	812	880	934	993	1059	1107	1161	1215	D	1120	KG at	550	kPa
	DUAL	1361	1478	1601	1701	1810	1950	2014	2114	2241					

### LT235/85R16 LRE XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		250	280	310	350	380	410	450	480	520	550	S	3042	LBS at	80	PSI
LBS	SINGLE	1740	1862	1985	2205	2315	2425	2623	2755	2910	3042	D	2778	LBS at	80	PSI
	DUAL	3170	3390	3610	4012	4211	4410	4762	5014	5296	5556	S	1380	KG at	550	kPa
kPa	SINGLE	790	845	900	1000	1050	1100	1190	1250	1320	1380	D	1260	KG at	550	kPa
	DUAL	1440	1540	1640	1820	1910	2000	2160	2270	2400	2520					

### LT245/75R16 LRE XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		250	280	310	350	380	410	450	480	520	550	S	3042	LBS at	80	PSI
LBS	SINGLE	1700	1865	2030	2205	2335	2480	2625	2765	2900	3042	D	2778	LBS at	80	PSI
	DUAL	3090	3390	3690	4012	4250	4510	4762	5030	5280	5556	S	1380	KG at	550	kPa
kPa	SINGLE	790	845	920	1000	1060	1125	1190	1255	1315	1380	D	1260	KG at	550	kPa
	DUAL	1440	1537	1675	1820	1927	2045	2160	2280	2395	2520					

## WHEEL DIAMETER - 17"

### 7.50R17 LRD XCA

PSI		45	50	55	60	65	70	75	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		310	340	380	410	450	480	520	S	2800	LBS at	75	PSI
LBS	SINGLE	1860	2025	2185	2340	2495	2650	2800	D	2600	LBS at	75	PSI
	DUAL	3460	3760	4060	4350	4640	4920	5200	S	1270	KG at	520	kPa
kPa	SINGLE	840	900	990	1050	1130	1190	1270	D	1180	KG at	520	kPa
	DUAL	1560	1680	1840	1960	2100	2220	2360					

## WHEEL DIAMETER - 17.5"

In the load and inflation tables, **SINGLE** means an axle with one tire mounted on each end, while **DUAL** means an axle with two tires mounted on each end. The loads indicated represent the total weight of an axle end, in an RV application. When one axle end weighs more than the other, use the heaviest of the two end weights to determine the unique tire pressure for all tires on the axle. The maximum cold air pressure for each axle may vary, depending on their weights. These tables are applicable for all RV axles, whether or not they are power-driven.

**10R17.5 LRG** XZA®

PSI		85	90	95	100	105	110	115		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790						
LBS	SINGLE	3860	4005	4150	4300	4470	4640	4805		S	4805	LBS at	115	PSI
	DUAL	7280	7570	7860	8160	8470	8780	9080		D	4540	LBS at	115	PSI
kPa	SINGLE	1750	1820	1890	1950	2030	2110	2180		S	2180	KG at	790	kPa
	DUAL	3300	3440	3580	3700	3840	3980	4120		D	2060	KG at	790	kPa

**WHEEL DIAMETER - 19.5"**

**8R19.5 LRF** XZA®

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760						
LBS	SINGLE	2540	2680	2835	2955	3075	3195	3305	3415	3525		S	3525	LBS at	110	PSI
	DUAL	4920	5140	5360	5570	5780	6000	6200	6400	6610		D	3305	LBS at	110	PSI
kPa	SINGLE	1150	1220	1285	1340	1400	1450	1500	1550	1600		S	1600	KG at	760	kPa
	DUAL	2240	2340	2430	2520	2620	2720	2820	2920	3000		D	1500	KG at	760	kPa

**225/70R19.5 LRF** XZE®, XRV®

PSI		65	70	75	80	85	90	95		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		450	480	520	550	590	620	660						
LBS	SINGLE	2755	2895	3040	3195	3315	3450	3640		S	3640	LBS at	95	PSI
	DUAL	5200	5440	5720	6000	6230	6490	6830		D	3415	LBS at	95	PSI
kPa	SINGLE	1250	1310	1380	1450	1500	1570	1650		S	1650	KG at	660	kPa
	DUAL	2360	2460	2600	2720	2820	2940	3100		D	1550	KG at	660	kPa

**225/70R19.5 LRG** XZE®

PSI		65	70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		450	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	2755	2895	3040	3195	3315	3450	3640	3715	3845	3970		S	3970	LBS at	110	PSI
	DUAL	5200	5440	5720	6000	6230	6490	6830	6980	7230	7500		D	3750	LBS at	110	PSI
kPa	SINGLE	1250	1310	1380	1450	1500	1570	1650	1690	1740	1800		S	1800	KG at	760	kPa
	DUAL	2360	2460	2600	2720	2820	2940	3100	3160	3280	3400		D	1700	KG at	760	kPa

**245/70R19.5 LRF** XZE®, XRV®

PSI		80	85	90	95							MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660											
LBS	SINGLE	3640	3740	3890	4080							S	4080	LBS at	95	PSI
	DUAL	6830	7030	7310	7720							D	3860	LBS at	95	PSI
kPa	SINGLE	1650	1700	1770	1850							S	1850	KG at	660	kPa
	DUAL	3100	3180	3320	3500							D	1750	KG at	660	kPa

**245/70R19.5 LRG** XZE®

PSI		80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660	690	720	760						
LBS	SINGLE	3640	3740	3890	4080	4190	4335	4540		S	4540	LBS at	110	PSI
	DUAL	6830	7030	7310	7720	7880	8150	8600		D	4300	LBS at	110	PSI
kPa	SINGLE	1650	1700	1770	1850	1900	1970	2060		S	2060	KG at	760	kPa
	DUAL	3100	3180	3320	3500	3580	3700	3900		D	1950	KG at	760	kPa

**245/70R19.5 LRH** XZE®

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830						
LBS	SINGLE	3390	3570	3750	3925	4100	4270	4440	4610	4775	4940		S	4940	LBS at	120	PSI
	DUAL	6420	6760	7100	7430	7760	8080	8400	8720	9040	9350		D	4675	LBS at	120	PSI
kPa	SINGLE	1540	1610	1700	1770	1860	1930	2000	2090	2150	2240		S	2240	KG at	830	kPa
	DUAL	2920	3060	3220	3360	3520	3660	3780	3960	4080	4240		D	2120	KG at	830	kPa

**WHEEL DIAMETER - 22.5"**

In the load and inflation tables, **SINGLE** means an axle with one tire mounted on each end, while **DUAL** means an axle with two tires mounted on each end. The loads indicated represent the total weight of an axle end, in an RV application. When one axle end weighs more than the other, use the heaviest of the two end weights to determine the unique tire pressure for all tires on the axle. The maximum cold air pressure for each axle may vary, depending on their weights. These tables are applicable for all RV axles, whether or not they are power-driven.

**9R22.5 LRF**

**XZE®**

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720					
LBS	SINGLE	3370	3560	3730	3890	4080	4235	4390	4540	S	4540	LBS at	105	PSI
	DUAL	6540	6820	7100	7380	7720	8010	8300	8600	D	4300	LBS at	105	PSI
kPa	SINGLE	1530	1615	1690	1760	1850	1920	1990	2060	S	2060	KG at	720	kPa
	DUAL	2960	3100	3220	3340	3500	3640	3780	3900	D	1950	KG at	720	kPa

**10R22.5 LRF**

**XZE®**

PSI		70	75	80	85	90	95	100	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690					
LBS	SINGLE	4080	4280	4480	4675	4850	5025	5205	S	5205	LBS at	100	PSI
	DUAL	7720	8090	8460	8820	9170	9520	9880	D	4940	LBS at	100	PSI
kPa	SINGLE	1850	1940	2030	2120	2200	2280	2360	S	2360	KG at	690	kPa
	DUAL	3500	3660	3820	4000	4160	4320	4480	D	2240	KG at	690	kPa

**10R22.5 LRG**

**XZE®**

PSI		70	75	80	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760	790					
LBS	SINGLE	4080	4280	4480	4675	4850	5025	5205	5360	5515	5675	S	5675	LBS at	115	PSI
	DUAL	7720	8090	8460	8820	9170	9520	9880	10150	10420	10710	D	5355	LBS at	115	PSI
kPa	SINGLE	1850	1940	2030	2120	2200	2280	2360	2430	2500	2575	S	2575	KG at	790	kPa
	DUAL	3500	3660	3820	4000	4160	4320	4480	4600	4720	4860	D	2430	KG at	790	kPa

**11R22.5 LRG**

**XZA3®**

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720					
LBS	SINGLE	4530	4770	4990	5220	5510	5730	5950	6175	S	6175	LBS at	105	PSI
	DUAL	8760	9160	9520	9900	10410	10830	11250	11680	D	5840	LBS at	105	PSI
kPa	SINGLE	2050	2160	2260	2370	2500	2600	2700	2800	S	2800	KG at	720	kPa
	DUAL	3980	4160	4320	4500	4720	4920	5120	5300	D	2650	KG at	720	kPa

**11R22.5 LRH**

**XZA3®**

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	4770	4990	5220	5510	5730	5950	6175	6320	6465	6610	S	6610	LBS at	120	PSI
	DUAL	9160	9520	9900	10410	10830	11250	11680	11790	11900	12010	D	6005	LBS at	120	PSI
kPa	SINGLE	2160	2260	2370	2500	2600	2700	2800	2870	2940	3000	S	3000	KG at	830	kPa
	DUAL	4160	4320	4500	4720	4920	5120	5300	5360	5420	5450	D	2725	KG at	830	kPa

**235/80R22.5 LRG**

**XZE®, XRV®**

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	3470	3645	3860	3975	4140	4300	4455	4610	4675	S	4675	LBS at	110	PSI
	DUAL	6320	6630	7050	7230	7530	7940	8110	8390	8820	D	4410	LBS at	110	PSI
kPa	SINGLE	1570	1650	1750	1800	1880	1950	2020	2090	2120	S	2120	KG at	760	kPa
	DUAL	2860	3000	3200	3280	3420	3600	3680	3800	4000	D	2000	KG at	760	kPa

**255/80R22.5 LRG**

**XZE®, XRV®**

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	3875	4070	4300	4440	4620	4805	4975	5150	5205	S	5205	LBS at	110	PSI
	DUAL	7050	7410	7720	8080	8410	8820	9050	9370	9610	D	4805	LBS at	110	PSI
kPa	SINGLE	1760	1850	1950	2010	2100	2180	2260	2340	2360	S	2360	KG at	760	kPa
	DUAL	3200	3360	3500	3660	3820	4000	4100	4260	4360	D	2180	KG at	760	kPa

**255/70R22.5 LRH**

**XZE® \***

PSI		80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660	690	720	760	790	830					
LBS	SINGLE	4190	4370	4550	4675	4895	5065	5205	5400	5510	S	5510	LBS at	120	PSI
	DUAL	7940	8220	8550	8820	8910	9220	9350	9830	10140	D	5070	LBS at	120	PSI
kPa	SINGLE	1900	1980	2060	2120	2220	2300	2360	2450	2500	S	2500	KG at	830	kPa
	DUAL	3600	3720	3880	4000	4040	4180	4240	4460	4600	D	2300	KG at	830	kPa

In the load and inflation tables, SINGLE means an axle with one tire mounted on each end, while DUAL means an axle with two tires mounted on each end. The loads indicated represent the total weight of an axle end, in an RV application. When one axle end weighs more than the other, use the heaviest of the two end weights to determine the unique tire pressure for all tires on the axle. The maximum cold air pressure for each axle may vary, depending on their weights. These tables are applicable for all RV axles, whether or not they are power-driven.

**275/80R22.5 LRG** XZA3®

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	4500	4725	4940	5155	5370	5510	5780	5980	6175	S	6175	LBS at	110	PSI
	DUAL	8190	8600	9080	9380	9770	10140	10520	10880	11350	D	5675	LBS at	110	PSI
kPa	SINGLE	2040	2140	2240	2340	2440	2500	2620	2710	2800	S	2800	KG at	760	kPa
	DUAL	3720	3900	4120	4260	4440	4600	4780	4940	5150	D	2575	KG at	760	kPa

**275/80R22.5 LRH** XZE®, XZA3®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	4915	5175	5435	5690	5940	6190	6435	6680	6920	7160	S	7160	LBS at	120	PSI
	DUAL	9080	9560	10030	10500	10970	11430	11880	12330	12780	13220	D	6610	LBS at	120	PSI
kPa	SINGLE	2240	2340	2470	2570	2710	2800	2900	3030	3120	3250	S	3250	KG at	830	kPa
	DUAL	4120	4320	4560	4760	5000	5180	5360	5600	5760	6000	D	3000	KG at	830	kPa

**275/70R22.5 LRJ** XZA2® Energy™

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	4940	5170	5400	5625	5850	6070	6290	6510	6730	6940	S	6940	LBS at	130	PSI
	DUAL	9710	10160	10610	11050	11490	11930	12360	12790			D	6395	LBS at	120	PSI
kPa	SINGLE	2250	2340	2460	2550	2640	2750	2840	2950	3040	3150	S	3150	KG at	900	kPa
	DUAL	4420	4600	4820	5000	5180	5400	5580	5800			D	2900	KG at	830	kPa

**295/80R22.5 LRH** XZA2® Energy™

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	5375	5660	5940	6220	6495	6770	7040	7300	7570	7830	S	7830	LBS at	120	PSI
	DUAL	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	D	6940	LBS at	120	PSI
kPa	SINGLE	2440	2550	2700	2810	2960	3060	3170	3310	3410	3550	S	3550	KG at	830	kPa
	DUAL	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	D	3150	KG at	830	kPa

**295/60R22.5 LRJ** XZA2® Energy™

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	5260	5505	5750	5990	6230	6465	6700	6930	7160	7390	S	7390	LBS at	130	PSI
	DUAL	9650	10100	10550	10990	11430	11860	12290	12720	13140	13560	D	6780	LBS at	130	PSI
kPa	SINGLE	2390	2490	2610	2710	2800	2930	3020	3140	3230	3350	S	3350	KG at	900	kPa
	DUAL	4380	4560	4800	4980	5140	5380	5540	5760	5940	6150	D	3075	KG at	900	kPa

**305/70R22.5 LRL** XRV®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	5375	5660	5940	6220	6495	6770	7040	7300	7570	7830	S	7830	LBS at	120	PSI
	DUAL	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	D	6940	LBS at	120	PSI
kPa	SINGLE	2440	2550	2700	2810	2960	3060	3170	3310	3410	3550	S	3550	KG at	830	kPa
	DUAL	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	D	3150	KG at	830	kPa

**315/80R22.5 LRL** XZA2® Energy™, XZA® 1

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	6415	6670	6940	7190	7440	7610	7920	8270	8810	9090	S	9090	LBS at	130	PSI
	DUAL	11680	12140	12790	13090	13540	13880	14420	15220	16020	16540	D	8270	LBS at	130	PSI
kPa	SINGLE	2910	3030	3150	3260	3370	3450	3590	3750	3980	4125	S	4125	KG at	900	kPa
	DUAL	5300	5500	5800	5940	6140	6300	6540	6900	7240	7500	D	3750	KG at	900	kPa

**365/70R22.5 LRL** XZA®

PSI		80	85	90	95	100	105	110	115	120	125	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660	690	720	760	790	830	860					
LBS	SINGLE	7350	7710	8070	8430	8780	9130	9480	9820	10200	10500	S	10500	LBS at	125	PSI
	DUAL											D		LBS at		PSI
kPa	SINGLE	3320	3510	3660	3840	3980	4120	4300	4440	4620	4750	S	4750	KG at	860	kPa
	DUAL											D		KG at		kPa

In the load and inflation tables, **SINGLE** means an axle with one tire mounted on each end, while **DUAL** means an axle with two tires mounted on each end. The loads indicated represent the total weight of an axle end, in an RV application. When one axle end weighs more than the other, use the heaviest of the two end weights to determine the unique tire pressure for all tires on the axle. The maximum cold air pressure for each axle may vary, depending on their weights. These tables are applicable for all RV axles, whether or not they are power-driven.

**445/50R22.5 LRL** X One® XRV®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	6940	7310	7680	8030	8390	8740	9090	9370	9780	10200	S	10200	LBS at	120 PSI
	DUAL											D		LBS at	PSI
kPa	SINGLE	3150	3320	3480	3640	3810	3970	4120	4250	4430	4625	S	4625	KG at	830 kPa
	DUAL											D		KG at	kPa

**WHEEL DIAMETER - 24.5"**

**11R24.5 LRG** XZA3®

PSI		70	75	80	85	90	95	100	105		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720						
LBS	SINGLE	4820	5070	5310	5550	5840	6095	6350	6610		S	6610	LBS at	105	PSI
	DUAL	9320	9740	10140	10520	11020	11350	11680	12010		D	6005	LBS at	105	PSI
kPa	SINGLE	2190	2300	2410	2520	2650	2770	2890	3000		S	3000	KG at	720	kPa
	DUAL	4220	4420	4600	4780	5000	5160	5320	5450		D	2725	KG at	720	kPa

**275/80R24.5 LRG** XZA3®

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	4545	4770	4940	5210	5420	5675	5835	6040	6175		S	6175	LBS at	110 PSI
	DUAL	8270	8680	9080	9480	9860	10410	10620	10990	11350		D	5675	LBS at	110 PSI
kPa	SINGLE	2060	2160	2240	2360	2460	2575	2650	2740	2800		S	2800	KG at	760 kPa
	DUAL	3740	3940	4120	4300	4480	4720	4820	4980	5150		D	2575	KG at	760 kPa

